

Manual Daylight Dimmer installation guide

for Solatube® Brighten Up® Series 160DS & 290DS

This ceiling blind may be used with the Solatube Vusion™ or OptiView® ceiling diffuser.



Parts List	Qty
Ceiling mounted blind & frame assembly	1
Handle and pole assembly	1
Fixing kit containing:	1
frame screws	x 4
plaster board plugs	x 4
screw caps	x 4
handle & pole wall bracket	x 1
wall bracket screws	x 2
pole locator	x 1

Instructions:

1. Slide the pole locator onto the blind's tab to create a location point for the handle and pole.
2. With the blind mechanism open, position the frame on the ceiling as required, framing the diffuser centrally.
3. Mark the four fixing positions on the ceiling through the frame. Check no obstructions or utilities are behind the four fixing positions.
4. Remove the frame, then drill four holes into the ceiling at the marked positions and insert the plasterboard plugs.
5. Insert the screws through the screw cap ring and fix the frame to the ceiling.
(Warning: Do not over tighten the screws, particularly if the ceiling is uneven, as this may twist the frame and effect the smooth operation of the blind assembly)
6. Snap the cover caps over the screw heads.
7. Secure the handle & pole wall bracket to your preferred location with the wall bracket screws provided.
8. The blind may now be pulled across the frame to dim the light (using the pole if necessary).

Important notice

Please ensure that all components have arrived in perfect condition before starting the installation.
If any components are damaged in transit, the complete, unused system should be returned for replacement.
We do not accept return of individual system components.



SolaLighting Limited

Sola House, 17 High Street, Olney, Bucks, MK46 4EB

Tel 0845 4580101 / 01234 241466 Fax: 01234 241766 Web: www.solalighting.co.uk Email: solatube@solalighting.co.uk

Registered in England, 6 Corunna Court, Corunna Road, Warwick CV34 5HQ Registration No 3938764

©SolaLighting Limited 2007